




Wall Mount Sounders, PS1-T3

Product Overview:

The Pertronic PS1-T3 is a piezo-sounder suitable for surface or flush mounting in areas where aesthetics are important, such as apartment buildings.



PS1-WT3 (White)





PS1-RT3 (Red)

Features:

- » Generates the Evacuation tone as specified by ISO8201 (T3) or AS2220 (link selectable)
- » Normally connected to the monitored Warning System output of a Fire Alarm panel and is activated when the output circuit voltage polarity is reversed for the Alarm state
- » May be mounted in standard single-gang flush or surface mount electrical fittings and is supplied with a protective plastic cover for installation during building construction
- » Available with Red or White clip on cover


Tone Characteristics:




Specifications:

| | | |
|-----------------------------|---|--------------------------------------|
| » Dimensions | 117 x 74 x 12 | W x H x D mm (depth above Flush Box) |
| » Sound Level Output (peak) | Evacuation 12 Volt: High Volume – 95 dBA ± 3 dBA @ 1 m | |
| | Evacuation 24 Volt: High Volume – 98 dBA ± 3 dBA @ 1 m | |
| » Volume Control Range | 20 dB | |
| » Operating Voltage | 9.5 to 30 VDC | |
| » Quiescent Current | 0.2 µA @ 12 VDC | 0.4 µA @ 24 VDC |
| » Operating Current | ISO8201 (T3) | 9 mA Average, 25 mA peak @ 24 VDC |
| | AS2220 | 14 mA average, 28 mA peak @ 24 VDC |
| » Controls | Link selectable for T3 or AS2220 (default = No Link = T3) | |

Sound Pressure Distribution:



Connection Diagram:



Ordering Information:

| Product Code | Description |
|--------------|--|
| PS1-RT3 | Conventional Sounder (Red) with AUS T3 Tones |
| PS1-WT3 | Conventional Sounder (White) with AUS T3 Tones |