

Weatherproof Audio Visual Sign

Product Overview:

The Pertronic **Weatherproof Audio Visual Sign** provides reliable visual alerts as required by AS 4214 and ISO 14520, within a weatherproof enclosure and sounder. The device also produces clear audible tones and voice messages.

The Audio Visual Sign uses the latest LED technology to provide high visibility and improved performance compared to other technologies.

An on-board microcontroller provides eight stage-selectable backlight operating modes and a 90 second (maximum) Countdown Timer.

An optional LED display is available for visual indication of the Countdown Timer.

The Visual Sign supports 2-wire, 3-wire, or 4-wire standard connections.

Configuration DIP switches provide tone control for each of two stages.



Audio Visual Sign with Sounder (AVS-B-WP+S) fitted with optional Fire Alarm display and Red Fascia (AVD-FA-R)

Features:

- » Preloaded with 47 tones including ISO 8201 T3 Tone, AS 2220 Evacuation, Alert Tones and Voice Messages
- » Volume control for Tones and Voice messages
- » Dual stage configuration options
- » Optional LED Countdown display
- » Designed to meet IP66
- » Low current consumption
- » 2-wire, 3-wire, and 4-wire operation
- » Large range of visual messages available

Specifications:

»

Dimensions 280 x 280 x 135 $W \times H \times D mm$

Material ABS, Light Grey

Shipping Weight 2.0 kg

Cable Termination 0.5 mm² to 2.5 mm² **Operating Temperature Range** -10 °C to 70°C

Relative Humidity 10 % to 93% RH, non-condensing

Operating Mode 2-wire, 3-wire or 4-wire

Voltage Range 20 Vdc to 30 Vdc

Monitoring Voltage ≤ 0.5 V in 2-wire mode

Current @ 24 VDC 38 mA to 130 mA configuration dependent

Countdown Timer Up to 90 seconds optional

Backlight 8 operational combinations stage selectable using DIP switch **Audio Power**

1 watt @ 24 V (Tone)

Internal View:



Ordering Information:

Product Code	Description
AVS-B-WP+S	Audio Visual Sign, Weatherproof Version with Sounder (requires separate Fascia)
AVS-C-WP+S	Audio Visual Sign, Weatherproof c/w countdown timer & sounder ((requires separate Fascia)
AVD-ESI-A-WP	A/V Sign Fascia, Extinguishing System Inoperative, Amber, Weatherproof
AVD-FADNE-R-WP	A/V Sign Fascia, Fire Alarm, Do Not Enter, Red, Weatherproof
AVD-FAEA-R-WP	A/V Sign Fascia, Fire Alarm, Evacuate Area, Red, Weatherproof
AVDC-FADNE-R-WP	A/V Sign Countdown Fascia, Fire Alarm, Do Not Enter, Red, Weatherproof
AVSCM	Countdown Module for Audio-Visual Sign

0360 Weatherproof Visual Warning Sign Iss 2.1 20161222